Segura

PRODUCTINFORMATION

Species	European Ash
Surface texture	Brushed
Finish	Oil
Grade options	Plank: Prime Light Herringbone grades: Prime Light Chevron: Prime Light Tile: Prime Light
Construction	**Duoplank®** Engineered

DIMENSIONS

Thickness	15 mm (5/8")
Plank widths	180 mm (7")
Plank lengths	1080, 1230, 1480, 1800, 1980, 2230, 2480, 3000 mm (3'7", 48 7/16", 58 1/4", 70 7/8", 77 15/16", 87 13/16", 97 5/8", 9'10")
Herringbone dimensions	Tailor made
Tile dimensions	Tailor made

USAGE

Recommended usage	Suitable for use in all project sectors: Residential, Commercial, Hospitality, Retail, Yachting
Maintenance	Hakwood Clean & Hakwood Oil Care

INSTALLATION

Plank	Glue down 4-side tongue & groove
Herringbone	Glue down 1 side tongue, 2 side groove
Chevron	Glue down 1 side tongue, 2 side groove (includes left & right elements)
Tiles	Glue down 4 side groove

SUBFLOOR HEATING & COOLING

Compatibility	Guarantee available when installed and maintained in accordance with Hakwood Subfloor Heating & Cooling document

SUSTAINABILITY		TEST METHOD	CERTIFICATE/RESULT
	FSC certified (Mix)	FSC-STD-40-004	FSC® Certicate-Code: SCS-COC-000609
	Environment Product Declaration (EPD)	EN 15804 +A2 (+indicators A1)	MRPI Registration 1.1.00639.2024
	Indoor Air Comfort Gold	Different European and Asian regulations	LEED, BREEAM and WELL Compliant
	Indoor Air Comfort USA	CDPH/EHLB/Standard method V1.2	LEED Compliant
	Ecovadis	Sustainability rating	Bronze (Top 35% worldwide)

ENGINEERED WOOD FLOORING STANDARD		TEST METHOD	CERTIFICATE/RESULT
	CE (Conformité Européenne) European standard	EN 14342	CE Compliant
	UKCA (United Kingdom Conformity Assessment) United Kingdom standard	EN 14342	UKCA Compliant

LOW EMITTING MATERIALS		TEST METHOD	CERTIFICATE/RESULT
	E1 certificate	EN 717-7	E1 compliant & E2 compliant
	California Air Resources Board (CARB) Certificate for formaldehyde	ASTM E1333	CARB 2 Compliant
	Émissions dans l'air intérieur A + label France national Volatile Organic Compound (VOC) A+ label	ISO 16000p 3,6,9	A+ very low-emission
	AgBB German label for low emissions	ISO 16000	AgBB Compliant
	CA 01350 California Section 01350 Test for VOC Emissions	CDPH/EHLB/Standard method V1.2	LEED Compliant

SLIP RESISTANCE		TEST METHOD	CERTIFICATE/RESULT
	Unpolished Slip Resistance Value	CEN/TS 15676	59 USRV
	Anti-slip property Angle of acceptance	DIN 51130	R9 (range 6°-10°)
	Anti-slip property Angle of inclination	DIN 51097 / GUV-I 8527	B

SOUND REDUCTION		TEST METHOD	CERTIFICATE/RESULT
	Impact sound reduction	EN ISO 140-8 EN ISO 717-2	15mm (5/8"): 16dB [Lw] 20mm (3/4"): 14dB [Lw]

SCRATCH RESISTANCE		TEST METHOD	CERTIFICATE/RESULT
	Scratch resistance	DIN 68861	4E

REACTION TO FIRE		TEST METHOD	CERTIFICATE/RESULT
	EN14342 Wood flooring - characteristics, evaluation of conformity and marking	EN 13501-1	15mm (5/8"): Cfl-s1
		ASTM E648	15mm (5/8"):Class II

The Netherlands
+31 183 504 266
sales@hakwood.com

United States
+1 630 219 3388
ussales@hakwood.com

Dubai
+971 555 069 524
hwme-sales@hakwood.com

HAKWOOD