Vedetta



PRODUCTINFORMATION

	Species	European Oak
	Surface texture	Brushed
	Finish	Oil
	Grade options	Plank: Prime, Refined, Premier 1-bis, Exclusive, Select, Balanced, Natural, Standard, Classical Herringbone grades: Refined, Balanced Chevron: Prime, Refined, Premier 1-bis, Select, Balanced, Natural, Classical Tile: Prime, Premier 1-bis
	Construction	**Duoplank®** Engineered

DIMENSIONS

	Thickness	14*, 15, 20 mm (9/16"*, 5/8", 3/4")
	Plank widths	110, 142, 180, 240, 300 mm (4 11/32", 5 9/16", 7", 9 1/2", 11 13/16")
	Plank lengths	1080, 1220, 1470, 1790, 1970, 2220, 2470, 3000 mm (3'7", 4', 4'10", 5'11", 6'6", 7'3", 8'1", 9'10")
	Herringbone dimensions	80 x 480 mm (3 5/32" x 18 29/32")
	Chevron	45°: 110 x 550, 142 x 660 mm (4 11/32" x 21 21/32", 5 9/16" x 25 31/32") 60°: 110 x 510, 142 x 510 mm (4 11/32" x 20 1/16", 5 9/16" x 20 1/16")
	Tile dimensions	Tailor made
		**Only available in 180 mm (7") width*

USAGE

	Recommended usage	Suitable for use in all project sectors: Residential, Commercial, Hospitality, Retail, Yachting
	Maintenance	Hakwood Clean & Hakwood Oil Care

INSTALLATION

	Plank	Glue down 4-side tongue & groove
	Herringbone	Glue down 1 side tongue, 2 side groove
	Chevron	Glue down 1 side tongue, 2 side groove (includes left & right elements)
	Tiles	Glue down 4 side groove

SUBFLOOR HEATING & COOLING

Compatibility	Guarantee available when installed and maintained in accordance with Hakwood Subfloor Heating & Cooling document	

SUSTAINABILITY	TEST METHOD	CERTIFICATE/RESULT
FSC certified (Mix)	FSC-STD-40-004	FSC® Certicate-Code: SCS-COC-000609
Environment Product Declaration (EPD)	EN 15804 +A2 (+indicators A1)	MRPI Registration 1.1.00639.2024
Indoor Air Comfort Gold	Different European and Asian regulations	LEED, BREEAM and WELL Compliant
Indoor Air Comfort USA	CDPH/EHLB/Standard method V1.2	LEED Compliant
Ecovadis	Sustainability rating	Bronze (Top 35% worldwide)

ENGINEERED WOOD FLOORING STANDARD	TEST METHOD	CERTIFICATE/RESULT
CE (Conformité Européenne) European standard	EN 14342	CE Compliant
UKCA (United Kingdom Conformity Assessment) United Kingdom standard	EN 14342	UKCA Compliant
NWFA (National Wood Flooring Association) United States standard	ANSI/HPVA EF2009	NWFA Compliant

LOW EMITTING MATERIALS	TEST METHOD	CERTIFICATE/RESULT
E1 certificate	EN 717-7	E1 compliant & E2 compliant
California Air Resources Board (CARB) Certificate for formaldehyde	ASTM E1333	CARB 2 Compliant
Émissions dans l'air intérieur A + label France national Volatile Organic Compound (VOC) A+ label	ISO 16000p 3,6,9	A+ / very low-emission
AgBB German label for low emissions	ISO 16000	AgBB Compliant
CA 01350 California Section 01350 Test for VOC Emissions	CDPH/EHLB/Standard method V1.2	LEED Compliant

SLIP RESISTANCE	TEST METHOD	CERTIFICATE/RESULT
Unpolished Slip Resistance Value	CEN/TS 15676	59 USRV
Anti-slip property Angle of acceptance	DIN 51130	R9 (range 6°-10°)
Anti-slip property Angle of inclination	DIN 51097 / GUV-I 8527	B

SOUND REDUCTION	TEST METHOD	CERTIFICATE/RESULT
Impact sound reduction	EN ISO 140-8 EN ISO 717-2	15mm (5/8"): 16dB [Lw] 20mm (3/4"): 14dB [Lw]

SCRATCH RESISTANCE	TEST METHOD	CERTIFICATE/RESULT
	DIN 68861	4E

REACTION TO FIRE		TEST METHOD	CERTIFICATE/RESULT
	**EN14342** Wood flooring - characteristics, evaluation of conformity and marking	EN 13501-1	14mm (9/16"): Dfl-s1 15mm (5/8"): Cfl-s1 20mm (3/4"): Cfl-s1
	**Flame spread & smoke development**	ASTM E648	15mm (5/8"): Class II 20mm (3/4"): Class II

The Netherlands
+31 183 504 266
sales@hakwood.com

United States
+1 630 219 3388
ussales@hakwood.com

Dubai
+971 555 069 524
hwme-sales@hakwood.com

HAKWOOD